

DELTA[®]-FOXX

Installation Instructions

- 1. Run the individual sheets parallel to the eaves and overlap by 10-15 cm. If the slope of the roof is up to a maximum of 6° below standard pitch, the overlap should be 15 cm wide.
- 2. If any structural components come up through the roof, DELTA[®]-FOXX must be run up these structures and fixed in such a way as to stop any penetration by rain or snow. A channel made out of DELTA[®]-FOXX should be made on the upper side of such structures to guide rain and molten snow into the adjacent rafter spaces.
- 3. DELTA[®]-FLEXX-BAND or DELTA[®]-THAN sealant can be used to make seals even more secure.
- 4. The bottom end of the DELTA[®]-FOXX should finish up on the gutter flashing or under the gutter board (not in the gutter).
- 5. DELTA[®]-FOXX should be run up the side of chimneys, skylights and other large structures that come up through the roof, attached with DELTA[®]-THAN and physically secured. Corners should be sealed with DELTA[®]-FLEXX-BAND.
- 6. We recommend applying DELTA[®]-NAGELDICH-TUNGSBAND. In this way, you can stop damp getting in through at the points where the membrane is fixed to counter and supporting battens.

You will find detailed installation instructions for DELTA[®]-FOXX on the internet at www.doerken.de in the form of a PDF file for you to print out and save.



Fax: +49 23 30/63-355

Dörken GmbH & Co. KG
Wetterstraße 58
D-58313 Herdecke

Request for tender DELTA[®]-FOXX/DELTA[®]-FOXX PLUS

Item No.	Qty.	Specifications	Price/unit	Price total
1 m ²	<p>DELTA[®]-FOXX (manufacturer: Dörken GmbH & Co. KG, D-58311 Herdecke) – to be supplied and laid on a skinned surface as a diffusive sheathing membrane made of polyester fabric with a dispersion coating in accordance with roofing regulations and manufacturer's instructions. To be fixed onto the sheathing using staples or wide-head nails. In overlap areas, the nails or staples securing the DELTA[®]-FOXX should be concealed.</p> <p>Fire resistance Class E (EN 13501-1) Tensile strength approx. 370/270 N/5cm (EN 12311-1) S_d value approx. 0.02 m Weight approx. 270 g/m²</p>		
2 m ²	<p>DELTA[®]-FOXX PLUS (manufacturer: Dörken GmbH & Co. KG, D-58311 Herdecke) – to be supplied and properly laid as a diffusive sheathing membrane made of polyester fabric with a dispersion coating and integrated self-adhesive border in accordance with roofing regulations and manufacturer's instructions. To be fixed onto the rafters using staples or wide-head nails.</p> <p>Fire resistance Class E (EN 13501-1) Tensile strength approx. 370/270 N/5cm (EN 12311-1) S_d value approx. 0.02 m Weight approx. 270 g/m²</p>		
3 nos	<p>Joints between DELTA[®]-FOXX and skylights or dormer windows, glass tiles, chimneys etc. should be formed so that water cannot get in, but is guided past via a channel in the sheet at the point where the cut-out occurs.</p>		
4 /m	<p>DELTA[®]-NAGELDICHTUNGSBAND to be supplied and stuck on the DELTA[®]-FOXX beneath the counter battens.</p>		